


弯折参考图



IMD	MPU Interface
0	80-16 BIT,DB0~DB15 used
1	80-8 BIT,DB8~DB15 used

PIN	SYMBOL
1	DB0
2	DB1
3	DB2
4	DB3
5	GND
6	IOVCC(3V)
7	/CS
8	RS
9	/WR
10	/RD
11	IM0
12	X+ /NC
13	Y+ /NC
14	X- /NC
15	Y- /NC
16	LEDA
17	LEDK1
18	LEDK2
19	LEDK3
20	LEDK4
21	NC
22	DB4
23	DB8
24	DB9
25	DB10
26	DB11
27	DB12
28	DB13
29	DB14
30	DB15
31	/RESET
32	VCI(3V)
33	IOVCC(3V)
34	GND
35	DB5
36	DB6
37	DB7

Specification:

- 1). Display type: a-si 262K TFT/Transmissive
- 2). Viewing angle: 12 O'clock
- 3). Operating temp.: -20°C~+60°C
Storage temp.: -30°C~+70°C
- 4). IC: ILI9341
- 5). Backlight: 4 chip White LED ,in parallel

更改记录

标记	日期	更改内容	制图

河北冀诚电子有限公司

制图	型号	GTF-02806V3
	编号	02806V3-0
	日期	2015.05.16
	分号	3
	页数	1 / 1
	单位: mm	
	未注公差 ±0.2	

