



〈双面电极,元件在背面〉

PIN	NAME	PIN	NAME
1	XR	26	DB7
2	YD	27	DB6
3	XL	28	DB5
4	YU	29	DB4
5	GND	30	DB3
6	NC	31	DB2
7	NC	32	DB1
8	IM0/ID	33	DB0
9	IM1	34	DOUT
10	IM2	35	DIN/SDA
11	RESX	36	RDX
12	VSYNC	37	WRX/SCL
13	HSYNC	38	D/CX
14	PCLK	39	CSX
15	DE	40	TE
16	DB17	41	IOVCC
17	DB16	42	VCI
18	DB15	43	GND
19	DB14	44	LEDA
20	DB13	45	LEDK1
21	DB12	46	LEDK2
22	DB11	47	LEDK3
23	DB10	48	LEDK4
24	DB9	49	LEDK5
25	DB8	50	LEDK6

NOTES:

1. DISPLAY TYPE:TFT-TRANSMISSTIVE-POSITIVE-MONO
2. VDDI:5.0V
3. OP. TEMP. : -20° C — 70° C
ST. TEMP. : -30° C — 80° C
4. VIEWING ANGLE:(U/D/L/R) 70/60/70/70
5. DRIVER IC:COG/ILI9487、ILI9488
6. ROHS CERTIFICATED
7. LED Voltage:3.1V

更改记录

标记	日期	更改内容	制图

河北冀诚电子有限公司

制图	型号	GTF-03508
	编号	03508-0
	日期	2015.04.23
	分号	3
	页数	1 / 1
	单位	mm
	未注公差	±0.2

