


PIN NO.	SYMBOL
1	/CS
2	/RES
3	A0
4	/WR
5	/RD
6-13	DO-D7
14	VDD
15	VDD
16	VDD
17	VSS
18	VSS
19	VSS
20	V0
21	V0
22	XV0
23	XV0
24	VG
25	VG
26	C86
27	PS
28	NC
29	NC
30	NC
31	NC
32	NC
33	NC

NOTES:

- DISPLAY TYPE: A: STN-TRANSMISSIVE-NEGATIVE-BLUE
B: FSTN-TRANSMISSIVE-POSITIVE-ANTI-UV
- VDD=3.3V VLCD=9.5±0.3V
- OPERATING TEMPERATURE: 0°C~50°C
- STORAGE TEMPERATURE: -10°C~60°C
- DRIVE MODE: 1/65D,1/9B
- VIEWING DIRECTION: 6:00
- CONNECTOR: COG/ST7567
- NO BACK LIGHT

SCALE B



更改记录

标记	日期	更改内容	制图
△	2013.03.26	增加FSTN模式	

河北冀诚电子有限公司

制图	型号	GTK-345V10
	编号	345V10-0
	日期	2013.03.26
	分号	3
	页数	1/1
	单位	mm
	未注公差	±0.3

