



No.	PIN	No.	PIN
1	NC	14	D3
2	VDD	15	D4
3	Vss	16	D5
4	BM0	17	D6
5	BM1	18	D7
6	WR1	19	VSS
7	WRO	20	NC
8	CD		
9	CS1		
10	RST		
11	D0		
12	D1		
13	D2		



NOTE:

1. DISPLAY MODE:FSTN, POSITIVE/TRANSFLECTIVE
2. VIEWING DIRECTION:6 O' CLOCK
3. OPERATION TEMP:-20° C - +70° C
4. STORAGE TEMP:-30° C - +80° C
5. DRIVE METHOD:1/160 DUTY, 1/10BIAS, ①VOP=12.5V, ②VOP=14.5V
6. DRIVE IC: UC1611X
7. BACKLIGHT:YELLOW-GREEN EDGE LED, ILED=60mA@VLED=4.1V, CUSTOMER MUST ADD A CURRENT LIMIT RESISTOR, OR USING IN CONSTANT CURRENT MODE.

Modify History				GEM-TECH ELEC. CO.,LTD.			
Mark	Date	Description	Drwn.	Drwn.	P. N.	GTK-387	
					File No.	387-0	
				Chk.	Date:	2013. 11. 13	
				Apr.	Sub. No.	3	Page 1/1
					Unit:	mm	
					Unmark Tolerance:	±0.3	

